

BETTER **IN** ROTARY VALVES

Rotary Airlocks and Blowing Seals



 **tbma**

www.tbma.com

SAMPLING • DOSING • MIXING • STORAGE • CONVEYING • DEDUSTING • DISCHARGING • FILLING • ENGINEERING

HIGH DUTY



Type H-AR

Application:

- Mounted below powder hoppers or as dust explosion barrier
- Dosing, pneumatic conveying

Features:

- ATEX 95 certified
- Flange size: DN 150 - DN 500
- Volume: 2,5 - 125 ltr/rev
- Body and end covers: cast iron or stainless steel
- Corrosion/abrasion resistant coatings optional
- Rotor: steel or stainless steel
- 8 fixed or 9 adjustable rotor blades
- Outboard, dust-tight ball bearings
- Max. operating pressure differential 1,5 bar
- Certified dust-explosion and flameproof up to 10 bar



Type H-GR

Application:

- Pneumatic conveying

Features:

- ATEX 95 certified
- Flange size: DN 150 - DN 350
- Volume: 2,5 - 58 ltr/rev
- Body and end covers: cast iron or stainless steel
- Corrosion/abrasion resistant coatings optional
- Rotor: steel or stainless steel
- 8 fixed or 9 adjustable rotor blades
- Outboard, dust-tight ball bearings
- Max. operating pressure differential 1,5 bar



Type H-AX

Application:

- Mounted below powder hoppers for abrasive and/or mildly cohesive products
- Dosing, pneumatic conveying.

Features:

- ATEX 95 certified
- Flange size: DN 150 - DN 350 (square/circular)
- Volume: 2,5 - 34 ltr/rev
- Body and end covers: cast iron/steel
- Corrosion/abrasion resistant coatings optional
- Rotor: steel or stainless steel
- 8 fixed or 9 adjustable rotor blades
- Outboard, dust-tight ball bearings
- Max. operating pressure differential 1,5 bar

MEDIUM DUTY



Type R-AX

Application:

- Mounted below powder hoppers for abrasive and/or mildly sticky products
- Dosing, pneumatic conveying of non-abrasive products

Features:

- ATEX 95 certified
- Flange size: DN 150 - DN 350 (square/circular)
- Volume: 2,5 - 34 ltr/rev
- Body and end covers: cast iron/steel
- Corrosion/abrasion resistant coatings optional
- Rotor: steel or stainless steel
- 8 fixed or 9 adjustable rotor blades
- Max. operating pressure differential 1 bar



Type M-AX

Application:

- Mounted below powder hoppers for abrasive and/or mildly sticky products
- Dosing, pneumatic conveying of non-abrasive products

Features:

- ATEX 95 certified
- Flange size: DN 150 - DN 350 (circular)
- Volume: 2,5 - 58 ltr/rev
- Body and end covers: cast iron/steel
- Corrosion/abrasion resistant coatings optional
- Rotor: steel or stainless steel
- 8 fixed or 9 adjustable rotor blades
- Max. operating pressure differential 1 bar



Type S-AX

Application:

- Below dust filters and cyclones

Features:

- ATEX 95 certified
- Flange size: DN 250 (square/circular)
- Volume: 9,5 ltr/rev
- Body and end covers: SmartLite™ cast iron
- Rotor: steel
- 8 blade rotor with Polyurethane blade tips
- Max. operating pressure differential 0,5 bar
- Certified dust-explosion and flameproof up to 1.14 bar

SmartLite™

SPECIAL DUTY

Application:

- Accurate discharge of poor flowing products
- Volumetric and gravimetric dosing
- Pneumatic conveying



Type HZ

Features:

- ATEX 95 certified
- Flange size: DN 150 - DN 700
- Volume: 0,5 - 60 ltr/rev
- Construction: steel or stainless steel
- Corrosion/abrasion resistant coatings optional
- Special agitators available for poor flowing products

ATEX 95



Special executions

- Quick-release rotor in various executions
- High temperature resistant execution up to 450°C
- Larger executions available up to 547 ltr/rev
- Sanitary valve execution
- Mobile valve execution
- Pulsed air injection system

tbma europe bv

P.O. Box 140 NL-2210 AC
Delfweg 18 NL-2211 VM
Tel.: +31(0)252 37 50 68
E-mail: info@tbma.com

Noordwijkerhout - Holland
Noordwijkerhout - Holland
Fax: +31(0)252 37 54 36
www.tbma.com

For more information